

Small in size, big in performance!



Key features:

- Lightweight aluminium frame
- Strong thermoplastic shroud
- Retractable handle and wheels for easy manoeuvrability
- ON / OFF- switch
- Individually suspended glass-fibre reinforced propeller blades
- Angle adjustment: up to - 20 ~ + 50°
- Connection cable 4 meters with 230V (IP68) earthing contact plug

Options for E- Motor PPV Direkt drive

- Spiral ducts
- Spray mist ring
- Low Noise Impeller
- High-Expansion Foam Adapter / AdFoam
- EEx / Explosion proof electric motor
- Mains Connection 400V/50Hz

Specification

	18E2,2	21E2,2	24E2,2
Item No	736-1800-22-0	736-2100-22-0	736-2400-22-0
Air Volume AMCA 210	15.000m ³ /h	20.000m ³ /h	23.000m ³ /h
Air Volume AMCA 240	20.000m ³ /h	25.000m ³ /h	27.000m ³ /h
Effective air output injector principle	> 35.000m ³ /h	> 50.000m ³ /h	> 55.000m ³ /h
Fan Diameter	18"(457mm)	21"(533mm)	24"(610mm)
Motor	E-Motor, 230V, 50Hz, 2,2kW, Degree of protection IP 55, air cooled		
mains connection	230V, 50Hz		
Dimension (w x h x d)mm	585x550x440mm	665x625x450mm	755x705x450mm
Weight ca.	30kg	32kg	ca.37kg
Additional model features	Retractable handle and wheels for easy manoeuvrability		



- Angle adjustment: up to - 20 ~ + 50°



We therefore reserve the right to amend specifications without notice or obligation