



Great in performance, compact, reliable!

Key features

- Electro polished stainless steel frame
- Direct-driven ppv
- Retractable handle and tyres for easy manoeuvrability
- Strong thermoplastic shroud
- Single suspended fiberglass-reinforced fanblades
- Angle adjustment $-20 \sim +20^\circ$

Gasoline driven ppv fans

Options for Gasoline driven TYPHOON

- Exhaust hose (1,4 Meter)
- Spray mist pipes:
- *Spray mist ring*
- Spiral duct for forced and exhaust ventilation
- High-Expansion Foam Adapter /
- AdFoam-18"- 27"

Specification

	18H5-DD	21H6.5-DD	24H9-DD	27H9-DD	27H13-DD
Item No	545-3650-10-DD	545-3660-10-DD	545-3670-20-DD	545-3620-00-DD	545-3690-00-DD
Air volume (AMCA210)	16.000m ³ /h	20.500m ³ /h	23.100m ³ /h	27.100m ³ /h	31.000m ³ /h
Air volume (AMCA240)	> 27.200m ³ /h	> 36.000m ³ /h	> 40.000m ³ /h	> 42.000m ³ /h	> 50.000m ³ /h
Effective air output injector principle	> 44.800m ³ /h	> 57.000m ³ /h	> 81.000m ³ /h	> 81.000m ³ /h	> 81.000m ³ /h
RPM	3600	3600	3400	3200	3500
Diameter, fan	18 inch (457mm)	21 inch (533mm)	24 inch (610mm)	27 inch (686mm)	27 inch (686mm)
Fan blades	anti-static, glass reinforced, polyamide blades				
Motor	Honda GX160/ 3,6kW(4,9hp), Air cooled,4-stroke, recoil start	Honda GX200 / 4,1kW(5,6hp), Air cooled,4-stroke, recoil start	Honda GX270/ 6,3kW(8,6hp), Air cooled,4-stroke, recoil start	Honda GX270/ 6,3kW(8,6hp), Air cooled,4-stroke, recoil start	Honda GX390, 8,7kW(11,8hp), Air cooled,4-stroke, recoil start
Dimensions (h x w x d)mm	570 x 540 x 500	670 x 625 x 550	740 x 705 x 580	830 x 790 x 590	850 x 790 x 600
Weight: Netto / Brutto(with gasoline)	31,6kg / 35kg	36,8kg / 41kg	51kg / 57kg	51kg / 57kg	63kg / 69 kg



Angle adjustment: till $-20 \sim +20^\circ$

