

Options / Equipment

High-Expansion Foam Adapter AdFoam-18"-30"



High-expansion foam adapter for gasoline- electro- and water- driven high performance fans



Spiral duct for forced and exhaust ventilation



Diameter range: 18", 21", 24", 27", 30" inch
Length of ducting: From 5 up to 7,5 m. Intermediate lengths are possible. The helix, made of PVC coated spring steel wire for corrosion protection, is welded on externally.

Pitches: 150 mm
Suspension: optional
 1 row of galvanized suspension hooks, tear strength approx. 50 kp

Each length of ducting has flexible endrings at both ends, made of PVC coated spring steel wire. Cuff ends are available on request.



Connection clamp with knee lever

Knee lever belt allows an easy and quick installation without additional tools or installation facilities!

One-way air ducting / PE-sleeve for foam delivery.



Diameter range: 18", 21", 24", 27", 30" inch

Various lengths: up to 100 Meter

Spray mist ring



Art.Nr. SP0350_R

Spray Mist



Art.Nr. SP0450_R

With the spray nozzle up to 15 l / min of water can be injected into the air stream. All you have to do is connect the water hose with the quick coupling to the spray nozzle

Spray mist pipes



Art.Nr. SP0021-00




For the subsequent mounting on petrol and electric driven devices

Spray pipes are mounted with just a few swift moves even on already delivered fans. The spray mist pipes are delivered with C-Storz couplings

Dimensions (H x B x T): 800 x 500 x 200mm
Weight: 5,0 kg


Reversible Impeller



For positive pressure and suction.

Reversible Impeller for uses with the need for reversible current directions.

Blades with Airfoil Profile



- Extremely low noise levels
- Lower absorbed power
- Improved efficiency

Personal security



Art.Nr. 351 000

! Only for E-Fans !

Abdeckhaube

